


SOLAR PANEL MONOCRYSTALLINE

40W MAXX

36 cells
Monocrystalline

40W
Maximum power




MAXX


TECHNICAL DATA

INDEX	P0005
MODEL TYPE	40W Maxx
Peak power (Pmax) [W]	40
Maximum Power Voltage (Vmp) [V]	18,00
Maximum Power Current (Imp) [A]	2,22
Open Circuit Voltage (Voc) [V]	21,60
Short Circuit Current (Isc) [A]	2,39
Maximum System Voltage	1000VDC(IEC)
Power Tolerance	0 ~ +3%
Cell Type	Monocrystalline
Dimensions [mm]	530x510x25
Weight [kg]	3,20
Output cables	90cm 2x2,5mm MC4
Warranty	5 years
Bus Bar	5BB
Junction box	IP65
Front Glass (tempered glass)	3,2mm
Frame	black

TECHNICAL DRAWING (mm)



CHARAKTERISTICS



ISO9001
ISO14001
OHSAS18001
IEC TS 62941



BIS



The electrical parameters listed on the product label may differ slightly from the specifications.

4sun

4Sun sp. z o.o. sp.k.

Annopol 4, 03-236 Warszawa

tel: (22) 114 98 05, email: biuro@4sun.eu

www.4sun.eu