

Charging regulator

LS0512EU 5A

Product code: R0019

10A

Rated current

PWM

Type



FUNCTIONS

- Easy and quick change of battery type selection with the push of a button
- USB output for charging mobile devices (smartphone, tablet, etc.).
- Bright and clear charge status display and four battery charge levels.
- Electronic protection against overvoltage, short circuits, reverse polarity, overloads


4sun®

TECHNICAL DATA


INDEX	R0019
MODEL	LS0512EU 5A
Nominal system voltage	12VDC
Battery type	Sealed/Gel/Flooded
Working voltage [V]	8~16
Rated charging current [A]	5
Rated discharge current [A]	5
Maximum PV circuit voltage [V]	30
Charging voltage [V]	14,6
Low-voltage cut-off voltage [V]	11,1
Connection voltage [V]	12,6
Own consumption	12V≤5mA; 24V≤7mA
Efficiency	≤95%,(N.C.)
Protection	IP20
Warranty	2 years
Equalisation voltage [V]	Sealed: 14,6
Dimensions (L x W x H) [mm]	109,7x65,5x20,8
Weight (g)	90
Temperature range	-35°C~+55°C

APPLICATION


Solar Car




Solar Home




Solar Backpack



Solar Boat



Solar Street Light



Solar Power Generator

