

Charging regulator

VS6048AU 60A

Product code: R0060

60A

Rated current

PWM

Type



FUNCTIONS

- Protects against overcharging, deep discharge, surges, short circuits, reverse polarity, and overloads.
- Three-stage PWM charging (Bulk, Boost/Equalize, Float) with support for various battery types (sealed, gel, flooded).
- Multiple load control modes, including manual mode, light control, Dual Time, and debugging mode.
- Clear LCD display and dual USB output for monitoring and connecting devices.
- Battery temperature monitoring and compensation for optimal performance.


4sun®

TECHNICAL DATA


INDEX	R0060
MODEL	VS6024AU 60A
Nominal system voltage	12/24/36/48VDC Auto
Battery type	Sealed/Gel/Flooded
Working voltage [V]	9~64
Rated charging current [A]	60
Rated discharge current [A]	60
Maximum PV circuit voltage [V]	96
Charging voltage [V]	14,6
Low-voltage cut-off voltage [V]	11,1
Connection voltage [V]	12,6
Own consumption	12V≤5mA; 24V≤7mA
Efficiency	≤95%,(N.C.)
Protection	IP30
Warranty	2 years
Equalisation voltage [V]	Sealed: 14,6
Dimensions (L x W x H) [mm]	214x128,7x72,2
Weight (g)	1040
Temperature range	-25°C~+55°C

APPLICATION


Solar Car




Solar Home




Solar Backpack



Solar Boat



Solar Street Light



Solar Power Generator

