## **Charging** regulator

## MPP165 DUO DIG 10A

Product code: 1710

10A

**MPPT** 

Rated current

Type



## **FUNCTIONS**


- Overcharge protection and reverse current blocking (night mode) protect the batteries from damage and prevent reverse current flow at night.
- Protection against overload, overheating, short circuit, and reverse polarity enhances system safety and reliability.
- Automatic voltage drop compensation on charging cables ensures efficient charging by compensating for losses in the cables.
- Compatibility with Solar-Computer S, VPC, Bluetooth connection, and solar current display output (EBL) facilitates integration with various monitoring and control systems.



TECHNICAL DATA	
INDEX	1710
MODEL	MPP165 DUO DIG 10A
Nominal system voltage	12 VDC
Battery type	Sealed/Gel/Flooded
Maximum module power [Wp]	165
Maximum solar module current [A]	10
Grid suppression filter	YES
Maximum PV module voltage [V]	50
Charging line characteristics	IU1oU2
Battery charging I/II max [A]	11,8/1,0
Current consumption in sleep mode	4 mA
EBL combinability	YES
Reverse current protection	YES
Overcharge protection	YES
Warranty	2 years
Ambient temperature	- <b>20</b> °C∼+ <b>45</b> °C
Dimensions (L x W x H) [mm]	131x40x77
Weight (g)	190
Connection for temperature sensor	YES

## **APPLICATION**








Solar Backpack





Solar Street Light

