## **Charging** regulator

## BlueSolar MPPT 150/100

Product code: SCC115110420

100A Rated current MPPT Type



## **FUNCTIONS**

- Ultraspeed Maximum Power Point
  Tracking (MPPT) improves energy harvesting
  by up to 30% compared to PWM charge
  controllers and by up to 10% compared to slower
  MPPT controllers, especially under
  varying light conditions.
- Advanced Maximum Power Point
  Detection in partial shading the innovative
  SmartSolar algorithm maximizes energy capture
  by identifying the optimal MPP in challenging
  conditions.
- Exceptional conversion efficiency, achieving over 98% efficiency without the need for a cooling fan, which increases energy efficiency.
- Fully programmable charging algorithm with eight pre-programmed charging modes, easily selectable via a rotary switch.
- Built-in Bluetooth Smart module allows wireless configuration, monitoring, and system synchronization, as well as access to additional features like Smart Battery Sense or SmartShunt



TECHNICAL DATA	
INDEX	SCC115110420
MODEL	BlueSolar MPPT 150/100
Nominal system voltage	12/24/48 VDC Auto
Battery type	Liq.,Gel, Acid, AGM
Maximum PV input power [W]	1450/2900/4350/5800
Rated charging current [A]	100
Rated discharge current [A]	100
Maximum PV circuit voltage [V]	145
Maximum continuous load current [A]	100
Power supply connections [mm <sup>2</sup> ]	35
Charging algorithm	adaptive
Self-consumption	≤35mA(12V); ≤20mA(48V)
Temperature compensation	16mV/-32mV/-64mV/°C
Protection	IP43, IP22
Warranty	2 years
Efficiency	98%
Dimensions (L x W x H) [mm]	216x295x103
Weight (g)	4500
Temperature range	-30°C∼+60°C

## **APPLICATION**











