

Charging regulator

SmartSolar MPPT 75/15

Product code: SCC075015060R

15A

Rated current

MPPT

Type



FUNCTIONS

- The SmartSolar charge controller can recharge even a severely depleted battery, as long as the cells are not permanently damaged.
- Built-in Bluetooth allows for remote control and monitoring of the charger via the VictronConnect app, while the Victron Remote Management (VRM) portal provides access to charger functions from anywhere.
- The intelligent load output feature prevents battery damage caused by over-discharge by automatically disconnecting the load at a set voltage.
- The SmartSolar controller ensures daily battery recharge to 100%, even in adverse conditions, by gradually increasing the disconnect voltage, which extends battery life.
- The ability to monitor MPPT even in remote locations without internet access is provided by the GlobalLink 520 device.


4sun®

TECHNICAL DATA

INDEX	SCC075015060R
MODEL	SmartSolar MPPT 75/15
Nominal system voltage	12/24 VDC Auto
Battery type	Liq., Gel, Acid, AGM
Maximum PV input power [W]	220/440
Rated charging current [A]	15
Rated discharge current [A]	15
Maximum PV circuit voltage [V]	75
Maximum continuous load current [A]	15
Power supply connections [mm ²]	6
Charging algorithm	adaptive
Self-consumption	19mA (12V); 16mA (24V)
Temperature compensation	-16mV/-32mV/°C
Protection	IP43, IP22
Warranty	2 years
Efficiency	98%
Dimensions (L x W x H) [mm]	100x113x40
Weight (g)	500
Temperature range	-30°C~+60°C

APPLICATION


Solar Car




Solar Home




Solar Backpack



Solar Boat



Solar Street Light



Solar Power Generator

