

Charging regulator

SmartSolar MPPT 100/30

Product code: SCC110030210

30A

Rated current

MPPT

Type



FUNCTIONS

- The SmartSolar charge controller can recharge even a severely depleted battery, as long as the cells are not permanently damaged.
- Built-in Bluetooth allows for remote control and monitoring of the charger via the VictronConnect app, while the Victron Remote Management (VRM) portal provides access to charger functions from anywhere.
- The intelligent load output feature prevents battery damage caused by over-discharge by automatically disconnecting the load at a set voltage.
- The SmartSolar controller ensures daily battery recharge to 100%, even in adverse conditions, by gradually increasing the disconnect voltage, which extends battery life.
- The ability to monitor MPPT even in remote locations without internet access is provided by the GlobalLink 520 device.


4sun®

TECHNICAL DATA


INDEX	SCC110030210
MODEL	SmartSolar MPPT 100/30
Nominal system voltage	12/24 VDC Auto
Battery type	Liq., Gel, Acid, AGM
Maximum PV input power [W]	440/880
Rated charging current [A]	30
Rated discharge current [A]	30
Maximum PV circuit voltage [V]	100
Maximum continuous load current [A]	30
Power supply connections [mm ²]	16
Charging algorithm	adaptive
Self-consumption	30mA(12V); 20mA(24V)
Temperature compensation	-16mV/-32mV/°C
Protection	IP43, IP22
Warranty	2 years
Efficiency	98%
Dimensions (L x W x H) [mm]	130x186x70
Weight (g)	1300
Temperature range	-30°C~+60°C

APPLICATION


Solar Car




Solar Home




Solar Backpack



Solar Boat



Solar Street Light



Solar Power Generator

