


SOLAR PANEL MONOCRYSTALLINE 200W BF MAXX

64 cells
Monocrystalline

200W
Maximum power




MAXX


TECHNICAL DATA

INDEX	P0187
MODEL	200W BF Maxx
Peak Power (Pmax) [W]	200
Maximum Power Voltage (Vmp) [V]	22,48
Maximum Power Current (Imp) [A]	8,90
Open Circuit Voltage (Voc) [V]	26,29
Short Circuit Current (Isc) [A]	9,37
Maximum System Voltage	1000VDC(IEC)
Power Tolerance	0~+3W
Cell Type	Monocrystalline
Dimensions [mm]	1485x668x30
Weight [kg]	10,5
Output cables	90cm 2x4.0mm ² MC4
Warranty	5 years
Bus Bar	12BB
Junction box	IP68
Front Glass (tempered glass)	3,2mm
Frame	black

TECHNICAL DRAWING (mm)



CHARACTERISTIC



ISO9001
ISO14001
OHSAS18001
IEC TS 62941



BIS



The electrical parameters listed on the product label may differ slightly from the specifications.

4sun®

4Sun sp. z o.o. sp.k.
Annopol 4, 03-236 Warszawa
tel: (22) 114 98 05, email: biuro@4sun.eu

www.4sun.eu