

SZ-70-40M

Warranty

- 5 years Manufacturer Warranty
- Warranty on Electrical Performance: 10 years 90% + 25 years 80% of power output

Manufacturing

- Original cell sorting system ensures the best electric cell match
- EL-Testing before packing.
- Comprehensive module power testing.

Performance

- Higherer module efficiency and compact size. Weakened hot-spot effect, lower module failure
- rate and increased stability by shingle-tech.
- Special connection method lowers the internal resistance and ensures better performance than traditional connection with busbar.
- IP67 rated junction box, reliable cables and standard MC4 connectors improve the stability



Mechanical Data

Standard Test Conditions AM=1.5, E=1000W/m², TC=25°C

Nominal Power	70W
Cell Type	Monocrystalline
Module Efficiency	19.05%
Maximum Power Current (Impp)	3.74A
Maximum Power Voltage (Vmpp)	18.70V
Open-circuit Voltage (Voc)	22.10V
Short-circuit Current (Isc)	4.01A
Maximum System Voltage	500V
Output Tolerance	±3%
Cable	500mm / 2.5mm ²
Connector Type	None
Module Structure	Aluminum Frame / Glass / EVA / Backsheet
Junction box rating	≥IP67
Diode	✓
Working Temperature	-40°C~+80°C

Packaging

Module Dimensions	1050*350*30mm
Module Weight	4.60kg
Package	Single Package
Pieces per Pallet	Free
Gross Weight per Pallet	Free
Pallet Dimensions	Free

