

SOLAR PANEL MONOCRYSTALLINE

150W MAXX




MAXX

TECHNICAL DATA

INDEX	P0217
MODEL	150W Maxx
Peak Power (Pmax) [W]	150
Maximum Power Voltage (Vmp) [V]	19,47
Maximum Power Current (Imp) [A]	7,71
Open Circuit Voltage (Voc) [V]	22,83
Short Circuit Current (Isc) [A]	8,15
Maximum System Voltage	1000VDC(IEC)
Power Tolerance	+3%
Cell Type	Monocrystalline
Dimensions [mm]	1080x670x30
Weight [kg]	7,40
Output cables	90cm 2x4mm
Warranty	5 years
Bus Bar	12BB
Junction box	IP67
Front Glass (tempered glass)	3,2mm
Frame	black

TECHNICAL DRAWING (mm)




The dimensions given are measured to the center of the mounting hole.


Differences between individual batches may be ± 5 mm.

CHARACTERISTIC

current-voltage



power-voltage



ISO9001
ISO14001
OHSAS18001
IEC TS 62941



BIS



The electrical parameters listed on the product label may differ slightly from the specifications.

4sun

4Sun sp. z o.o. sp.k.
Annopol 4, 03-236 Warszawa
tel: (22) 114 98 05, email: biuro@4sun.eu

www.4sun.eu