


# SOLAR PANEL MONOCRYSTALLINE

## 420W MAXX

108 cells  
Monocrystalline

420W  
Maximum power




# MAXX

### TECHNICAL DATA

INDEX	PD0001
MODEL	420W Maxx
Peak Power (Pmax) [W]	420
Maximum Power Voltage (Vmp) [V]	32,23
Maximum Power Current (Imp) [A]	13,03
Open Circuit Voltage (Voc) [V]	38,57
Short Circuit Current (Isc) [A]	13,96
Maximum System Voltage	1000VDC
Power Tolerance	+3%
Cell Type	Monocrystalline
Dimensions [mm]	1722x1134x30
Weight [kg]	20,5
Output cables	35cmx2x4mm MC4
Warranty	5 years
Temperature range [°C]	-40 ~ +85
Junction box	IP68
Glass thickness (tempered glass)	3,2mm
Frame	black
Wind load	2400Pa
Snow load	5400Pa


### TECHNICAL DRAWING (mm)



The dimensions given are measured to the center of the mounting hole.

Differences between individual batches may be  $\pm 5$ mm.

### CHARACTERISTIC



ISO9001  
ISO14001  
OHSAS18001  
IEC TS 62941



BIS



The electrical parameters listed on the product label may differ slightly from the specifications.

**4sun**

4Sun sp. z o.o. sp.k.  
Annopol 4, 03-236 Warszawa  
tel: (22) 114 98 05, email: biuro@4sun.eu

[www.4sun.eu](http://www.4sun.eu)