


# Tangra™ M HD Black

## 490–510W

N-Type High efficiency Monofacial Single Glass Module



30-year lifespan delivers 10-30% more power compared with conventional P-type modules



The natural lack of LID in the N-type solar cell can increase power generation



Excellent low irradiance performance



Better light trapping and current collection to improve module power output and reliability



Industry-leading, lowest thermal coefficient



Optimized electrical design and lower operating current for reduced hot spot loss and better temperature




Certified to withstand 2400 Pa of wind load and 5400 Pa of snow load



100% triple EL test, which greatly reduces the hidden cracks rate

## LINEAR PERFORMANCE WARRANTY



**15** years

Product quality & process guarantee

**30** years

Linear power guarantee

**0.40** %

Annual degradation

## COMPREHENSIVE CERTIFICATES



ISO 9001: Quality Management System

ISO 14001: Environmental Management System Standard

ISO 45001: International Occupational Health and Safety Assessment System Standard

SA8000: 2014 Social Accountability Management System

## WARRANTY INSURANCE



Warranty partner

Munich RE



\* Optional performance warranty insurance. Please contact our local sales staff for more information.

\* Different markets have different certification requirements. Also, the products are under rapid innovation. Please confirm the certification status with regional sales representatives.

## ELECTRICAL CHARACTERISTICS

Model of modules	SS-490-54MDH-G11(T)		SS-495-54MDH-G11(T)		SS-500-54MDH-G11(T)		SS-505-54MDH-G11(T)		SS-510-54MDH-G11(T)	
	STC	NMOT								
Maximum power – $P_{mp}$ (W)	490	375	495	378	500	382	505	386	510	390
Open-circuit voltage – $V_{oc}$ (V)	39.50	37.40	39.80	37.70	40.10	38.00	40.40	38.30	40.70	38.60
Short-circuit current – $I_{sc}$ (A)	15.80	12.74	15.83	12.76	15.86	12.78	15.89	12.80	15.92	12.82
Maximum power voltage – $V_{mp}$ (V)	32.88	31.08	33.10	31.30	33.30	31.52	33.50	31.73	33.70	31.94
Maximum power current – $I_{mp}$ (A)	14.91	12.05	14.97	12.08	15.03	12.11	15.08	12.15	15.13	12.19
Module efficiency – $\eta_m$ (%)	21.7		21.9		22.1		22.3		22.5	
Power tolerance (W)	(0,+5)									
Maximum system voltage (V)	1500									
Maximum rated fuse current (A)	25									
Current operating temperature (°C)	-40~+85 °C									

**STC** (Standard Testing Conditions): Irradiance 1000W/m<sup>2</sup>, Cell Temperature 25 °C, Spectra at AM1.5

**NMOT** (Nominal Module Operating Temperature): Irradiance 800W/m<sup>2</sup>, Ambient Temperature 20°C, Spectra at AM1.5, Wind at 1m/s

## STRUCTURAL CHARACTERISTICS

Module dimensions (L*W*H)	1996x 1134 x 30 mm
Weight	23.8 kg
Number of cells	108 cells
Cell	N-type monocrystalline
Glass	Tempered, 3.2 mm AR, high transmittance, low iron
Frame	Black anodized aluminum alloy
Junction box	IP68, 3 bypass diodes
Output wire	4.0 mm <sup>2</sup> , wire length: 300mm/1200mm/customized
Connector	MC4 Compatible
Mechanical load	Snow load: 5400 Pa * / Wind load: 2400 Pa ☼


## TEMPERATURE PERFORMANCE RATINGS

Temperature coefficient ( $P_{max}$ )	-0.30%/°C
Temperature coefficient ( $V_{oc}$ )	-0.28%/°C
Temperature coefficient ( $I_{sc}$ )	+0.04%/°C
Nominal Module Operating Temperature	43±2 °C

## PACKAGING CONFIGURATION

Container	40HQ
Quantity/pallet	36
Pallets/container	22
Quantity/container	792

## MODULE DIMENSIONS (MM)



\* The unmarked tolerance is ±1 mm  
Length shown in mm

